



























## **References**

- [1] T. Ishida and K. Aoki, "Airflow simulation Relative to Door Closing Operability," *SAE International. JSAE 20037016.01 2743*, 2003.
- [2] Y. L. Lee and H. S. Hwang, "Flow characteristics in a cabin during door closure," *IMechE . Automobile Engineering*, vol. 225 Part D, 2010.
- [3] D. A. Wagner and S. Seth, "Modelling the Effect of Cabin Air Pressure on Door Closing for the Door System Modeller," Ford Technical Research, SRM-006, 1995.
- [4] M. Schumack , M. Abdul-Haq, A. Shah and K. Eugene, "Air Pressure Efforts on Door – Closing Efforts," Ford Technical Research, 1994.
- [5] R. Bhsngsle and K. Mansinh, "Investing Factors Affecting Door Slam Noise of SUV and Improved Performance by DFSS Approach," *SAE International*, pp. 10.4271-01-1595, 2011.
- [6] E. Dikmen and I. Basdogan, "Experimental and Numerical Study for Determining the Mechanical Properties of Automobile Weatherstrip Seals," *Proceedings of ESDA2006 8th Biennial ASME Conference on Engineering Systems Design and Analysis*, 2006.
- [7] R. H. Myers and D. C. Montgomery, *Response Surface Methodology- Process and Product Optimization Using Designed Experiments*, Arizona: Arizona State University, 1995.
- [8] J. Zhou, "Robustness Design Case Study-Air Management for Closing Efforts Reduction," Ford Technical Research., 1994.