

been dwindled due to overexploitation, poor management, and its lack of natural durability. It is suspected to have been attacked by insects and fungi and its service life is low due to years on ground contact.

Perforated and split bamboo can be recommended for design of minor structural importance e.g lintel, but further research can be made on bamboo itself if there will be preservatives which can control the attack of insects and fungi when using it as reinforcing concrete in other to avoid voids within the concrete.

References

- [1] V. Afroughsabet, L. Biolzi, and T. Ozbakkaloglu, "High-performance fiber-reinforced concrete: a review," *J. Mater. Sci.*, vol. 51, (14), pp. 6517-6551, 2016.
- [2] F. E. Brink and P. J. Rush, "Bamboo reinforced concrete construction," *US Naval Civil Engineering Laboratory, Port Hueneme, California*, 1966.
- [3] J. K. Sevalia, N. B. Siddhpura, C. S. Agrawal, D. B. Sha, and J. V. Kapadia, "Study on bamboo as reinforcement in cement concrete," *Int.JERA*, vol. 3, (2), pp. 1181-1190, 2013.
- [4] F. E. Brink and P. J. Rush, "Bamboo reinforced concrete construction," *US Naval Civil Engineering Laboratory, Port Hueneme, California*, 1966.

Biography

Opeyeolu Timothy Laseinde is currently a Senior Lecturer in the Mechanical and Industrial Engineering Department of the Faculty of Engineering and the Built Environment, University of Johannesburg, South Africa. He earned his Honours degree in Mechanical/Production engineering from the Abubakar Tafawa Balewa University, Bauchi, master's in mechanical engineering from the Federal University of Technology, Akure. He has a Ph.D. in Mechanical Engineering earned from the Federal University of Agric, Abeokuta. He has published papers in Journals and conferences. At the tertiary level, he has taught Introduction to Engineering, Quality Control, Engineering Mathematics, Engineering Physics and Computer Aided Design (CAD).